




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>E21D 9/10</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/43637</b>
			(43) International Publication Date: 27 July 2000 (27.07.00)
(21) International Application Number: PCT/AU00/00030		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 20 January 2000 (20.01.00)			
(30) Priority Data: PP 8224 20 January 1999 (20.01.99) AU			
(71) Applicant (for all designated States except US): TERRATEC ASIA-PACIFIC PTY. LTD. [AU/AU]; "Huntingfield Industrial Estate", Lot 17, Patriarch Drive, Kingston, TAS 7050 (AU).			
(72) Inventors; and		Published	
(75) Inventors/Applicants (for US only): PEACH, Anthony, John [AU/AU]; 36 Talone Road, Blackmans Bay, TAS 7052 (AU). JONES, Alwyn, Arthur [AU/AU]; 19 Pearl Place, Blackmans Bay, TAS 7052 (AU). JURASOVIC, Anton, Josep [AU/AU]; 30 Sinclair Avenue, West Moonah, TAS 7009 (AU). JOHNSTONE, Geoffrey, Peter [AU/AU]; 836 Sandy Bay Road, Sandy Bay, TAS 7005 (AU). CUSICK, Wayne, Anthony [AU/AU]; 13 Tanundal Street, Howrah, TAS 7018 (AU). SUGDEN, David, Burnett [AU/AU]; 33 Kingston Heights, Kingston Beach, TAS 7050 (AU).		With international search report.	
(74) Agent: GRIFFITH HACK; 3rd floor, 509 St. Kilda Road, Melbourne, VIC 3004 (AU).			

(54) Title: ROCK BORING DEVICE



## (57) Abstract

A rock boring device (10) including a rotary disc cutter (11). The disc cutter (11) is driven in an oscillating manner and also driven or free to nutate, and the device includes a mounting section (22) for the rotary disc cutter and a driven section (21), and wherein the mounting section (22) is angularly offset from the axis of the driven section whereby the rotary disc cutter will both oscillate and nutate.